Appendix B

Mixture Design Requirements for ASPHALT PAVEMENT MATERIAL (APM)

Agency: EPC Department of Public Works	Project Number:
Date: <u>5/19/2022</u>	Project Name: <u>AFR Resurfacing</u>
Project Special Provision Sheet for ASPHALT PAVEMENT MATERIAL (APM)	
This form is a mandatory part of the bid documents , and shall be filled out by the AGENCY for each mix specified. The Contractor shall include a copy of this form with each Mix Design submittal after the contract is awarded.	
Street Classification:	
Construction Application: XTop Lift XIntermediate Lift(s) XBottom Lift(s) Patching Other	
Aggregate Gradation: Grading ST Grading SXX Grading S Other Approved 2" to 3" thick lifts	
RAP Quantity, Maximum: 0% X20%	25%* Other
Mix Design Method & Compaction Level: (Chose one Method & one Traffic Level ⇒ Compaction Level).	
Superpave Gyratory, N _{design} : (See Table 3.01)	
N=50 X N=75 N=100	
Asphalt Binder:	
XPG 58-28 XPG 64-22 P	G 64-28 Other
	ent the Construction Specifications defining the contract specific to the Specifications for details.
*RAP above 20% must be approved by the governing agency prior to placement.	